



# Dry Fix™

## Damp Proof Course



Dry Fix™ is a Polyethylene Damp-course and Concealed Flashing barrier of impervious material, built in to prevent moisture movement to any part of a building requiring protection. It includes a waterproof strip barrier around an opening in a wall or door or at a roof junction.

Approved for use for separating timber, wood-based products and metal from concrete, masonry or brick; and, as a moisture barrier and flashing in masonry veneer constructed in accordance with NZBC Acceptable Solution E2/AS2 and NZS 4229.

### Dry Fix™ - Advantages

- Gives instant shape forming
- A replacement for Bitumen Paper
- Does not react with solvent treated timber
- Inert to most solvents
- Permanent life span non-degradable
- Easy to use
- Cost effective

### Technical Details

- Embossed both sides to a minimum thickness of 750 um
- CodeMark Certified
- Manufactured to AS/NZS2904 - 1995
- Impact resistant
- Black Flexible polyethylene Film
- Low Slip with a kinetic coefficient of friction
- Non-Slip as product is double embossed
- Roll core made from recycled cardboard
- Complies to the NZBC

### Applications

Used in the building industry to avoid moisture. It provides a complete and permanent moisture barrier in the protection against water damage to buildings through the walls and brickwork. Used around brick vents, timber framing, windows and door flashings.



Description	Roll Length	Masons Code
Dry Fix 50mm	30m	DPC50
Dry Fix 75mm	30m	DPC75
Dry Fix 90mm	30m	DPC90
Dry Fix 100mm	30m	DPC100
Dry Fix 150mm	30m	DPC150
Dry Fix 200mm	30m	DPC200
Dry Fix 250mm	30m	DPC250
Dry Fix 300mm	30m	DPC300
Dry Fix 400mm	30m	DPC400

