



WrapStrap™

House Wrap Strapping

SPECIFICATION



1. HT Green Concrete Underlay
2. Hydro™ Seal Bituminous treatment
3. Dry-Fix DPC
4. Building Wrap
- 5. Wrapstrap™**
6. Window Tape
7. Air Tight P.E.F Backing Rod

PRODUCT DESCRIPTION

WrapStrap™ is a - Non Stretch - Polythene embossed strap that is installed around the building wrap to keep the insulation in place and prevent it from bulging into the cavity for buildings with a drained cavity application.

PHYSICAL PROPERTIES

Fire rated building wrap (Masons FR1) held in place over insulation with wrap strapping keeps the insulation in place and prevents it catching fire to a tested standard.

COMPATIBILITY

Masons WrapStrap is compatible with all building wraps.

INSTALLATION

After the installation of building wrap the WrapStrap is strapped horizontally around the frame. The strapping can be secured with a staple, screw or nail. A common sense approach to the distance between the horizontal strapping must be used.

DURABILITY

Not less than 50 years for building wrap and strapping used where the cladding DURABILITY requirement or expected serviceable life is not less than 50 years.

Masons WrapStrap™	Roll Sizes	Masons Code
Blue pp strap 19mmx300m	H 19mm x L 300m	WRAPST19X300
Blue pp strap 25mmx250m	H 25mm x L 250m	WRAPST25X250