

BrickTies

Heavy Duty Brick Ties



New Zealand's only Brick Tie that holds a CodeMark Certification

Applications

- Can be used to tie any masonry veneer to a structural frame
- Suitable for Dry and Wet Bed applications

New Zealand Building Code Standard (NZBC)

- **CodeMark Certified**
- Masons Brick Ties are manufactured to comply with **AS/NZS2699.1.2000**

Physical Properties

- Rated **Heavy Duty (EH) Earthquake**
- Available in three lengths: 85 mm, 90mm, 110 mm & 135 mm
- Available in hot dipped galvanised & 316 stainless steel

The following is to be used as a guide only

HORIZONTAL	VERTICAL
400mm	500mm
450mm	450mm
600mm	400mm

Approx. 5 brick ties per m² | 100 ties per 1000 bricks



TIP: Use Masons Brick or Block Lock for masonry areas prone to cracking (external corners, stack bond, above windows, doors & openings)

Description	QTY	Building Zone	Masons Code
BrickTie 85mm - Hot dipped galvanised	250	Normal Zone	TIE85HD
BrickTie 85mm - Hot dipped galvanised	500	Normal Zone	TIE85HD(500)
BrickTie 85mm - in Bag - Hot dipped galvanised	500	Normal Zone	TIE85HDBAG500
BrickTie 85mm - Hot dipped galvanised with 270 Tek Screws 35mm	250	Normal Zone	TIE85HDSF30
BrickTie 90mm - Hot dipped galvanised	250	Normal Zone	TIE90HD
BrickTie 110mm - Hot dipped galvanised	250	Normal Zone	TIE110HD
BrickTie 135mm - Hot dipped galvanised	250	Normal Zone	TIE135HD
BrickTie 85mm - Stainless Steel	250	Sea-spray Zone	TIE85SS
BrickTie 85mm - Stainless Steel with 270 Steel Frame Tek Screws 35mm	250	Sea-spray Zone	TIE85SSSF30
BrickTie 90mm - Stainless Steel	250	Sea-spray Zone	TIE90SS
BrickTie 110mm - Stainless Steel	250	Sea-spray Zone	TIE110SS
BrickTie 135mm - Stainless Steel	250	Sea-spray Zone	TIE135SS

Also Available with steel frame Tek Screws