



CODEMARK™

Product Description

40 Below Window Tape is a self-adhesive flashing tape to seal around windows, doors, and other joinery openings as a secondary defence against water penetration.

Roll Sizes

H 75mm x L 20m H 150mm x L 10m
H 100mm x L 20m H 200mm x L 20m
H 150mm x L 20m

Certificate Holder

Masons Plastabrick Ltd

9A Parkhead Place
Albany Auckland 0632 NZ
0800 522 533
www.mpb.co.nz

Certification Body

CertMark International Pty Ltd

T/A CertMark New Zealand
ABN: 80 111 217 568
JAS-ANZ Accreditation No. Z4450210AK
PO Box 321 Tuakau 2121
+64 (09) 951 8246
www.CertMark.org

CERTIFICATE OF CONFORMITY

This is to certify that



40 Below Window Tape



Complies with the New Zealand Building Code:

1. B2.3.1 (b).
2. B2.3.2.
3. E2.3.2.
4. F2.3.1.

Product Purpose or Use

40 Below Window Tape is a self-adhered, flashing tape designed to protect windows penetrations from moisture infiltration. When integrated into the wall system and used properly, the tape will provide a secondary defence against water penetrating. 40 Below Window Tape can also be used as a Rigid Air Barrier Tape.

Subject to the following Conditions & Limitations:

- a. The certificate holder must maintain compliance with the conditions set out in Section 15 of the Building (Product Certification) Regulations 2008.
- b. This product can be applied in temperature ranges of between -40c to +65c.
- c. Ensure all surfaces to which 40 Below Window Tape is applied are clean, dry and free of dust.
- d. 40 Below Window Tape is to be applied only in areas as described in the Masons 40 Below Window Tape Installation Instruction April 2014 and on the packaging. It should not be used in areas where it has the potential to be exposed to heat such as chimney flues.
- e. When applying 40 Below Window Tape to LOSP treated timber, ensure the solvent has been allowed to flash off prior to installing the product. It is suggested that a minimum of one (1) week is allowed for.
- f. 40 Below Window Tape when used, installed and maintained in accordance with the requirements outlined in 40 Below Window Tape technical brochure April 2014, contributes to the requirements of Acceptable Solution E2/AS1, Clause 9.1.5 (b) (i).

John Thorpe
CertMark International Pty Ltd

19/05/2016
Date of Issue

CMA-CM40098
Certificate Number

- This certificate is issued by an independent certification body accredited by the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation & Employment (MBIE) under the Building Act 2004. MBIE does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms to the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. MBIE disclaims, to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the MBIE website, www.mbie.govt.nz
- This certificate may only be reproduced in its entirety.

