



MASONS
Designed Smart, Built Tough.

Admix

Masonry Bond



MASONS™ Masonry Bond is an acrylic latex cement modifier and bonding agent for concrete, mortar, plaster, repairs, floor toppings etc.

Uses

MASONS™ Masonry Bond is used for improving and bonding floor toppings, plasters and mortars, repairs of worn, damaged or spalled concrete, floor screeds and toppings and concrete repair systems. Ideal for use in outside applications subject to continual presence of water.

Advantages

- Provides excellent adhesion to concrete, masonry, plaster, fibre-cement board and most surfaces
- The specific formulation allows thin coatings to be applied in the application of floor toppings, concrete, mortar etc
- Greatly improves tensile, compressive and flexural properties allowing thin section application of concrete, mortar, floor toppings etc.
- Excellent bonding is achieved within hours of completion
- Is not affected by water in exterior situations
- Chemical and abrasion resistance is improved
- Available in a strong sturdy container and several different sizes
- Ready to use from the container





Masonry Bond

Application

All applications – must be made free of dust particles and loose material, a clean surfaces is essential (water blasting or washing may be required). Make sure there is no oils, waxes, curing compounds and oil paint etc. To ensure maximum adhesion – use a primer coat. Pre-dampen the surface brush with water, brush off any excess water, Tub or brush undiluted MASONS™ Masonry Bond into the surface avoiding puddling. For optimum results apply the mortar topping plaster, while the primer is still tacky.

In more difficult situations – such as permanent dampness, very dense floors, etc, make up a mix with a 1:1 mixture of MASONS™ Masonry Bond and water, added to give a brush able slurry, should be applied firmly on the surface with a brush or stiff broom and allowed to achieve initial set before the topping, mortar etc is applied

A typical mix – design for floor topping or patch repairing is, 2 to 3 clean dry sand, 1 cement with MASONS™ Masonry Bond, at the rate of 5 litres per 40 kg bag of cement, added to the mixing water.

IMPORTANT - SHAKE WELL BEFORE USE

Pre-Cautions

MASONS™ Masonry Bond is slightly alkaline, therefore skin contact should be avoided. Gloves and protective clothing should be worn. MASONS™ Masonry Bond is non-flammable. If splashed into the eyes irrigate with clean water and seek medical attention. If ingested, again seek medical attention.

Technical Service

For your nearest stockist or additional technical information on MASONS™ products and our wide range of sealing compounds, concrete admixtures and additives for the construction industry, contact MASONS™ on 0800 522 5333.

The above information is based on our best knowledge and presented in good faith and we believe it to be true and accurate, however, due to the variable nature of application the suitability of the product for the intended use is the sole responsibility of the user.

Description	Size	Code
Masonry Bond 5 Lt	5 Lt	MB005
Masonry Bond 20 Lt	20 Lt	MB020