



Gas Patio Heaters

Installation Instructions



Glass Top Assembly Instructions

1. The glass top for the patio heater comes flat packed wrapped in cardboard and paper within the patio heater out box. Remove the package carefully and place in flat surface.

2. CAREFULLY unwrap the glass package.

3. Locate the 4 black powder coated fittings that connect the vertical glass panels and top glass panels together. These have slots that allow movement such as expansion and contraction.

4. Move the patio heater to where it will principally be positioned. This should be on a firm flat surface. Use the two handles provided to gain additional purchase, fixing slots are located under the square collar (see note 5).

5. Position and place any white pebbles, logs or glow fame embers ensuring there is a pathway for the flame to travel upwards with minimal interference.

6. Remove the square collar from the top of the heater base, this is a gravity fit no tools required.

7. Glass clamps, the glass clamps are held in place by 2 screws, these may be loosened slightly to assist placing of the glass panels correctly then gently re tightened. Use the correct size Allen key. Do not over loosen or lose the screws, or over tighten the screws one once the glass is in place.

8. Place the taller section of glass panels into the glass clamps pressing gently and firmly. Repeat for remaining panels. Align panels so tops are the same height, horizontal and line up neatly at the edges. Re tighten glass clamp screws if you have loosened them, do not over tighten.

9. Replace square metal collar over the glass panels, ease this on. If it jams on the glass, remove it and gently reposition the glass panels. Slide the collar over the glass and place on the heater base.

10. Top glass section. This is a two-person job. Place the black metal connectors onto the smaller top glass panel, carefully move these above the upright glass panels and place the connector slots above the upright glass panels. Slide connectors and top panel down together, work together with your assistant to ensure connectors stay in place, are not forced, and all slots align with the glass panels.

11. When moving the heater on anything but smooth level flooring Masons recommends the horizontal glass top is removed (once heater is cool), together with the gas bottle. This avoids the possibility of the top panel falling during movement of the heater.

NB. The gas regulator has been changed to a NZ standard LPG gas regulator at the correct pressure for this appliance. The anti-tilt/tip over switch has been removed as no NZ compatible alternative was available. Kratki patio heaters are very stable especially when the gas bottle is installed in the base.

- Store in a sheltered place and ALWAYS turn off the gas bottle when not in use.
- Check regularly for leaks as with any LPG appliance using dilute soapy water in a spray bottle or similar.
- Masons recommends the patio heater should be checked annually by a gas fitter as is standard advice for all gas appliances in NZ to ensure optimum performance and safety.
- Masons offer a 12 months return to base warranty on manufacturing and components. To make a warranty claim, or to enquire about spare or replacement parts contact the reseller you bought the heater from or Masons with your proof for purchase.

These gas patio heaters are Kratki heaters and distributed by Masons

Call your Masons Rep for further information

South Island: **Riki 021 786 898** ● S & E Auckland, Coromandel & Wellington: **Josh 021 929 070**

Central North Island, Tauranga & BOP: **Arthur 021 772 925** ● W. & N Auckland & Northland: **Jacqueline 021 414 100**

masons.nz 0800 522 533