

MASONS 4.5 MM FIBRE CEMENT SOFFIT LINING

PURPOSE

Mason Plastabrick supplies 4.5 mm thick fibre cement sheet for use as a soffit lining for external eaves and verge projections.

EXPLANATION

Masons 4.5 mm fibre cement soffit lining is a non-structural, lightweight, smooth, flat sheet. It is manufactured from Portland cement, crystalline silica, fly ash and cellulose pulp and is defined as non-combustible in accordance with ISO 13501.1 or BS 476-4. Once coated with a paint system it is resistant to moisture and rot.

Available sheet size:

Length: 2440 mm, Width: 600 mm, Thickness: 4.5 mm



For further assistance please contact:

-  0800 522 533
-  info@mpb.co.nz
-  www.mpb.co.nz



SCOPE AND LIMITATIONS OF USE

Scope	Limitations
<p>Location</p> <p>In wind zones up to and including extra high, as defined in NZS 3604:2011 or a maximum permissible ultimate limit state (ULS) of 2.1 kPa.</p> <p>In all corrosion zones as defined in NZS 3604:2011.</p> <p>Any proximity to the relevant boundary.</p>	<p>➤ Where installed within 1 m of a relevant boundary, the balance of the roof, eave and wall structure must meet the relevant fire-related building code obligations.</p>
<p>Building</p> <p>On buildings where the primary roof structure complies with the New Zealand Building Code (NZBC) or for an existing roof structure where the designer and installer are satisfied that the existing framing is suitable for the intended building work.</p> <p>In conjunction with timber or light weight steel framing.</p>	



USEFUL INFORMATION

For information on the design, installation and maintenance of Masons 4.5 mm fibre cement soffit lining and for our warranty refer to www.mpb.co.nz.



PERFORMANCE CLAIMS

If designed, installed and maintained in accordance with all Masons Plastabrick's requirements, the Masons 4.5 mm fibre cement soffit lining will comply with or contribute to compliance with the following performance claims:

NZ Building Code clauses	Compliance statement	BASIS OF COMPLIANCE ¹ Demonstrated by
B1 Structure B1.3.1, B1.3.2, B1.3.3 (a, h, j, m & q), B1.3.4 (a, b, c, d)	ALTERNATIVE SOLUTION	<ul style="list-style-type: none"> Manufactured and tested to MS 1296:1992 [UAC Superflex, 12/2011], BBA Product Sheet 1 19/5636 [04/04/2019], or Tested to IS: 14862, ASTM D-1032, IS: 2380, ASTM C1185 for tensile strength, compressive strength, screw withdrawal strength, density, modulus of rupture [Chemical & Metallurgical Services, Chennai, 03/2017].
B2 Durability B2.3.1 (b)	ALTERNATIVE SOLUTION	<ul style="list-style-type: none"> Manufactured and tested to MS 1296:1992 [UAC Superflex, 12/2011] BBA Product Sheet 1 19/5636 [04/04/2019], or Tested to IS: 14862, ASTM D-1032, IS: 2380, ASTM C1185 for Freeze/Thaw [Chemical & Metallurgical Services, Chennai, 03/2017].
C3 Fire affecting areas beyond the fire source C3.7 (a)	ALTERNATIVE SOLUTION	<ul style="list-style-type: none"> Tested to BS 476: Part 4: 1970 [TUV SUD PSB Pte. Ltd, 03/2015] BBA Product Sheet 1 19/5636 [04/04/2019], or ISO 13501.1:2007 [BRE Global, 19/04/2014].
E2 External Moisture E2.3.2, E2.3.3, E2.3.5, E2.3.7 (a, b, & c)	ALTERNATIVE SOLUTION	<ul style="list-style-type: none"> Manufactured and tested to MS 1296:1992 [UAC Superflex, 12/2011], BBA Product Sheet 1 19/5636 [04/04/2019], or Tested to IS: 14862, ASTM D-1032, IS: 2380, ASTM C1185 for water permeability, absorption, soaking [Chemical & Metallurgical Services Chennai, 03/2017].
F2 Hazardous Building Materials F2.3.1	ALTERNATIVE SOLUTION	<ul style="list-style-type: none"> Ramco Hicem Fibre cement board safety data sheet [28/05/2020], or BBA Product Sheet 1 19/5636 [04/04/2019].

1. The Compliance Statement is the pass holder's statement that they have met their obligations under s14G(2) of the Building Act 2004.

SOURCES OF INFORMATION²

- BRE Global. [19/03/2014] *Classification of reaction to fire performance in accordance with EN 13501.1:2007 +A1:2009 on UCO Superflex*. Classification report number 292606.2 Issue 1. Retrieved from <https://drive.google.com/file/d/1xaAk9Q8oxzhQDxiMGMo2DvtVgw5jKvC/view>. [Accessed on 13/10/2021]
- Chemical & Metallurgical Services, Chennai. [13/03/2017] IS: 14862, ASTM D-1032, IS: 2380, ASTM C1185. Test Report No: CMS/LTR/T-11115-Y/2016-17. Retrieved from <https://www.ramcohicem.com/certifications.php>. [Accessed on 26/07/2021].
- Ramco Hicem. [28/05/2020] *Ramco Hicem Fibre Cement Board Safety Data Sheet. V2.0*. Retrieved from <https://www.ramcohicem.com/pdf/SDS.pdf>. [Accessed on 26/07/2021].
- TUV SUD PSB Pte. Ltd. [25/03/2015] BS 476: Part 4: 1970 Fire Test on Building Materials and Structures – Non-combustibility Test for Materials. Test Report No. 7191109051-MEC15/B4-YWA. Retrieved from <https://www.ramcohicem.com/pdf/Non%20Combustibility.pdf>. [Accessed on 26/07/2021].
- UAC Berhad. [12/2011] UCO Superflex. Retrieved from <https://uac.com.my/general-products/uco-superflex/>. [Accessed on 13/10/2021].
- BBA [04/04/2019]. Fibre cement wall boards UCO Superflex Product Sheet no.1 19/5636.

2. Sources of information also include the Building Act 2004 and its regulations, including the Building Code (Schedule 1 of the Building Regulations 1992), Acceptable Solutions and Verification Methods, and relevant cited standards.

Scan or click this QR code for a full download of Compliance Documentation for this pass™.
www.mpb.co.nz



NAME: Trent Mason

POSITION: Director

DATE OF FIRST ISSUE:

DATE OF CURRENT ISSUE:

Signed on behalf of Masons Plastabrick Ltd:

By signing this pass™ the signatory confirms that, in respect of the subject of this pass™, the company has met their s14G obligations under the Building Act 2004.

18a David Mccathie Place, Silverdale, Auckland 0932 > info@mpb.co.nz > 0800 522 533 > www.mpb.co.nz

This Product Assurance Supplier Statement (pass™) has been prepared by TBB in accordance with MBIE PTS guidelines and the recommendations of s9.2, Determination No. 2019-011 (issued 12 April 2019). TBB is ISO9001:2016 certified. Copyright © 2017, The Building Business Limited (TBB). All rights reserved.